

New Guard Coatings Group

A global reputation to protect.

You have acquired this data sheet from the New Guard Coatings Group.

All information listed is correct at the time of print.



uksales@newguardcoatings.com



+44 1937 586311

Global Head Office: New Guard Coatings Ltd, Sandbeck Way, Wetherby, Leeds, LS22 7DN





Product Data Sheet

Product Name:

Guard Aquatint (Swimming Pool Paint)

Description:

Water-based, quick-drying coating designed for application on to swimming pools and other similar substrates. Eggshell finish.

Uses:

Virtually odourless and non-hazardous. Excellent flexibility and strength, and excellent protection and adhesion. Easy to use and recommended for public sale. Smooth coating with reasonable anti-slip properties when wet.

Product Information:

Colours	White, Black, Aqua Blue (others available on request)
Pack Sizes	5 Litres, 20 Litres
Thinner	Tap Water
Theoretical Spreading Rate	10m ² per litre (approx)
Volume Solids	55% (depending on colour)
Dry Film Thickness (DFT)	55µm
Wet Film Thickness (WFT)	100µm
Flash Point	N/A
VOC Content	N/A

Surface Preparation:

Ensure surfaces are clean, dry and free from grease and other contamination before coating. Thoroughly degrease and where applicable, abrade to promote good adhesion of the coating. Complex structures may be more effectively cleaned by detergent pressure washing or steam cleaning.

Mixing Instructions:

It is essential that the material is thoroughly mixed before use.



Product Data Sheet

Application:

In order to achieve the recommended dft, additional coats may be required depending on the equipment used, spraying techniques and substrate profile. Air and surface temperature must be over 5°C during application.

Brush	Yes
Roller	Yes
Airless Spray	Yes
Conventional Spray	Yes (Add water if required)

Drying Times:

Please note drying times are based on temperature at 20°C.

Touch Dry	30 minutes
Recoatable	2-4 hours
Hard Dry	24-48 hours

Storage:

Keep material in original containers and use within 12 months of delivery. Materials not used should be resealed. Store in a cool, dry place and at temperatures no lower than 10°C.

Precautions:

Materials are both hazardous and flammable and therefore precaution measures should be taken and appropriate P.P.E worn in accordance with the Material Safety Data Sheets and regulations.

Health & Safety:

Please view the product Health & Safety Sheet for information in relation to hazardous identification, first aid measures, fire fighting, accidental release, handling, exposure control, personal protective equipment (P.P.E), disposal and regulatory information.

Additional Info:

The above information should be used as a guide only and is not a guarantee or warranty. New Guard Coatings Group and our supply partners and manufacturers have provided this information in good faith and is to the best of our knowledge correct at the time of print. 'Guard' is a brand owned by New Guard Coatings Group, but this does not imply the manufacture of such product.

Review:

Date of Print: April 2014 Last Review:

Global Head Office:

New Guard Coatings Ltd
Sandbeck Way
Wetherby
West Yorkshire
LS22 7DN

Tel: +44 (0)1937586311

Email: uksales@newguardcoatings.com

New Guard Coatings Group



www.newguardcoatings.com