



PEGAFIX[®] UNIVERSAL

Colourless impregnating primer

High fixing capacity.

PEGAFIX® UNIVERSAL

DESCRIPTION

Colourless impregnating primer based on acrylic hydrosols.

RECOMMENDED USE

On different porous and chalking substrates, before painting them with waterborne paints.

TECHNICAL DATA

Density (g/cm ³):	1,0
Gloss Level:	Gloss
Gloss level at 60°:	Glossy: > 80%
Solids Content in weight:	14 - 16 %
Solids content in volume:	14 - 16 %

DRY TIMES BY 20° C/RV 50%

Touch dry:	1 hour
Dry to handle:	4 hours
Dry to recoat:	2-4 hours
Fully cured:	24 hours

RECOMMENDED WET FILM THICKNESS

100 µm

RECOMMENDED DRY FILM THICKNESS

15 µm

THEORETICAL CONSUMPTION

Very porous substrates (concrete, bricks): 5 - 10 m²/l
Little porous substrates (plaster, porous paints for inside use): 15 - 20 m²/l

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Remove dust and / or clean carefully.
Blistering plaster has to be sanded slightly to ensure a good adhesion or an adhesion test has to be done in advance.

DIRECTIONS FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION CONDITIONS

> 5°C, < 90% R.H.

APPLICATION & THINNING: BRUSH

Apply undiluted.

APPLICATION & THINNING: ROLLER

Apply undiluted.

APPLICATION & THINNING: AIRLESS SPRAY

Nozzle: 11 - 15 / Pressure: 200 bars.
Apply undiluted.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Apply undiluted.

CLEANING OF EQUIPMENT / SPILLS

Water.

REMARKS

On low porosity substrates, Pegafix is preferred above Parafix and Porisol because of its better penetration characteristics.
Possible dried spots (on windows, floors, etc.) can be removed with Thinner 22.
When using on chalking substrates, always test for fixing suitability.

SAFETY DATA

VOC level:	0 g/l
VOC readymix:	0 g/l
VOC category:	A/g
VOC limit:	30 g/l
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 20/08/2020

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu