

A global reputation to protect.

The information herewith is given with the best of New Guard Coatings Group knowledge.

Rights are reserved to change and update the data without notice.

This information is not exhaustive and it is the user's responsibility to ensure that this data sheet is the most current by contacting their local New Guard Coatings Group branch prior to using the coating/product.

www.newguardcoatings.com

NORTH • SOUTH EAST • MIDLANDS • NORTH WEST • HULL • SCOTLAND

MAPEFLOOR WAX REMOVER

Special multi-action, de-waxing detergent for Mapelux cross bond, metallic wax





WHERE TO USE

Mapefloor Wax Remover is used in environments for civil use, such as shops, showrooms, apartments, offices etc., to remove surface films of old metallic wax from floors treated with Mapelux.

Mapefloor Wax Remover has been specially developed to remove metallic wax, especially Mapelux Lucida and Mapelux Opaca cross bond metallic waxes.

It may also be used for deep-down cleaning and for removing wax from linoleum and/or rubber floors (in the case of old floors with this type of material, test beforehand to check for colour-fastness).

Some application examples

De-waxing treatment for **Mapelux** protective films on resin floors made using the **Mapefloor System** and/or the **Ultratop System**, including those mixed with **Dynastone Color** or natural aggregates, in environments for civil use before re-waxing the floor.

TECHNICAL CHARACTERISTICS

Mapefloor Wax Remover is a multi-action, low-foaming wax-removal detergent for deep-down cleaning and removal of all types of metallic wax.

It is particularly suitable for removing old films of cross bond metallic wax, such as **Mapelux Lucida**/ **Mapelux Opaca**. Its deep-cleansing action attacks all the components in the wax film, and quickly emulsifies residual materials and dirt. The product contains a minimum of 90% of primary bio-degradable surfactant components and complete aerobic biodegradation, which conforms to Reg. (CE) N° 648/2004.

How to use

For normal metallic waxes, use at a concentration of from 5 to 10% (1/2-11 in 10 l of water). For cross bond metallic waxes such as **Mapelux**, use at a concentration of 15% (1.5 l in 10 l of water). Use a white cleaning disk, vacuum the surface and then rinse.

PACKAGING

Mapefloor Wax Remover is available in 10 kg cans.

STORAGE

Mapefloor Wax Remover can be stored for 12 months in its original packaging at a temperature between +10°C and +30°C. Protect from frost.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION



Mapefloor Wax Remover is corrosive and may cause serious burns. It is also harmful if swallowed and it may irritate the respiratory tract. When applying the product, we recommend the use of protective gloves and goggles and to take the usual precautions for handling chemical products. If the product comes into contact with the eyes or skin, wash immediately with plenty of clean water and seek medical attention.

We also recommend working in well ventilated areas and to protect the respiratory apparatus with a face mask. For further and complete information about the safe use of our product please refer to the latest version of our Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)	
PRODUCT IDENTITY	
Appearance:	liquid
Colour:	pink
Density (g/cm³):	1.009
Content of active substances (%):	44
pH of concentrated product:	11.7 ± 0.2
Ross Miles depth of foam (ASTM D.459/47):	0 after 3 minutes
Solubility in water:	soluble
Solubility in oil:	insoluble

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com



