



# New Guard Coatings Group

☐ A global reputation to protect.

The information herewith is given with the best of New Guard Coatings Group knowledge.

Rights are reserved to change and update the data without notice.

This information is not exhaustive and it is the user's responsibility to ensure that this data sheet is the most current by contacting their local New Guard Coatings Group branch prior to using the coating/product.

[www.newguardcoatings.com](http://www.newguardcoatings.com)

NORTH • SOUTH EAST • MIDLANDS • NORTH WEST • HULL • SCOTLAND



constructive solutions

# Nitoseal® MS50

## One part, general purpose building sealant

### Uses

Nitoseal MS50 is suitable for sealing joints in Concrete, Brickwork, Blockwork, Perimeter sealing around doors and windows, Non-trafficked floor joints.

### Advantages

- Excellent adhesion to most common building materials
- Single component with fast rate of cure
- Easy to apply at low temperature
- Can be applied to damp substrates
- Environmentally friendly
- Primer-less for most applications (see "Priming")
- Available in a range of colours (see "Properties")
- Isocyanate free technology

### Description

Nitoseal MS50 is a one part, medium modulus sealant based on hybrid silyl modified polyether technology.

### Specification

Where shown on the contract documents, the one part sealant shall be Nitoseal MS50 supplied by Fosroc. It shall provide good UV protection and have a movement accommodation factor of 20%.

### Properties

Form	<b>Smooth, non-slumping paste</b>
Flash point	<b>&gt;65°C</b>
Colour	<b>White, Grey, Black, Portland Buff, Rustic Red, Brown</b>
Movement accommodation factor	<b>20%</b>
Skinning time (@20°C / 50% RH)	<b>30 minutes</b>
Cure rate (@20°C/50% RH)	
24 hours	<b>: 3mm</b>
48 hours	<b>: 6mm</b>
72 hours	<b>: 8mm</b>
Application temperature	<b>: 5 - 50°C</b>
Typical hardness (Shore A at 20°C)	<b>: 45</b>
UV resistance	<b>: Good</b>

### Instructions for use

#### Preparation

Joint surfaces must be clean dry and free from all dirt, laitance, loose material and foreign matter. Remove all rust, scale and protective lacquers from metal surfaces. Removal can be achieved by rigorous wire brushing, grinding or grit blasting.

Joints in concrete should preferably be sawn. After sawing all saw slurry must be flushed away and the joint allowed to dry.

When resealing, the existing sealant should be removed from the joint and the arris cleaned back to sound clean concrete. All debris should be removed.

Any expansion joint filler must be checked to ensure it is tightly packed and no gaps or voids exist at the base of the sealing slot before positioning a bond breaker.

The use of a bond breaker is not required in expansion joints containing cellular polyethylene joint filler such as Hydrocell XL\*†. For construction or contraction joints, a bond breaker tape or back-up strip must be used.

Where a particularly neat finish is required, mask the face edges of the joint before sealing and remove immediately after tooling is completed.

#### Priming

In joints where limited movement is expected, a primer is not normally required. In joints subject to high movement or intermittent immersion during service, Fosroc Primer MS1 is recommended.

Prime the joint face using a clean, dry brush. Avoid over application of primer causing puddles in the bottom of the joint.

Nitoseal MS50 should be applied between 30 minutes and 4 hours after priming. If a joint is left unsealed for more than 4 hours, the primer should be removed by grit blasting or grinding and the joint reprimed. Please contact your local Fosroc representative for any clarifications on priming.

#### Application

Cut the end off the sachet and place in the Fosroc GX gun. Fit the nozzle and cut at 45° at a suitable size for sealing the joint. Extrude the sealant firmly into the joint.

Tool flush within 5 minutes of application to ensure good contact between the sealant and the substrate.

#### Cleaning

Clean tools immediately after use with Nitoflor Sol.

# Nitoseal® MS50

## Estimating

### Supply

**Nitoseal MS50** : 10 no x 600ml sachets per box.  
**Fosroc Primer MS1** : 200ml packs

### Guide to sealant quantities

Joint size in mm	Litre per metre run	Metre per 600ml sachet
6x10	0.060	10.00
12x10	0.120	5.00
20x20	0.400	1.50
25x12	0.300	2.00
30x15	0.450	1.33
40x20	0.800	0.75

0.5 litres of Fosroc Primer MS1 will be sufficient for 60m of joint. No allowance has been made for joint dimensions or wastage .

### Limitations

- For continuous water immersed conditions, use Nitoseal MS600
- For trafficked floor joints, use Nitoseal MS300
- Not suitable for contact with Bituminous materials.
- Not suitable for contact with solvents, oil or petrol.
- Overcoating of the sealant will reduce the MAF of the sealant.

## Storage

When stored in warehouse conditions below 35°C, Nitoseal MS50 will have a shelf life of 12 months.

## Precautions

### Health and safety

Nitoseal MS50 is considered safe in normal use. However, as with any material, good hygiene practices should be followed, i.e. keep out of eyes, do not consume, keep away from children and pets, wash hands thoroughly after use.

### Fire

Nitoseal MS50 is non flammable while Fosroc Primer MS1 is flammable. Please refer to the Material Safety Data Sheet for details.

### Additional Information

Fosroc manufactures a wide range of complementary products which include :

- waterproofing membranes & waterstops
- cementitious & epoxy grouts
- specialised flooring materials

For further information on any of the above, please consult your local Fosroc office - as below.

® Denotes the trademark of Fosroc International Limited

### Important note :

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.

#### telephone

++91 80-22240018/120

#### fax

++91 80-22233474

#### e-mail

india@fosroc.com

### Regional Offices



#### Fosroc Chemicals (India) Pvt. Ltd.

##### Head Office

111/3, Hafeeza Chamber II Floor,  
K H Road, PBNo. 2744, Bangalore 560027  
[www.fosroc.com](http://www.fosroc.com)

##### Bangalore

Shankar House, IV Floor  
1 & 18, RMV Extension  
Bangalore 560 080  
Ph:080-2361 3161/2361 2004  
Fax : 080-2361 7454  
email: Bangalore@fosroc.com

##### Mumbai

208/209, Persepolis  
Sector 17, Vashi  
Navi Mumbai 400 703  
Ph:022-2789 6412/14  
Fax: 022 - 2789 6413  
email:Mumbai@fosroc.com

##### Delhi

First floor, 1/2 East Patel Nagar  
Opp: Vivek Cinema, Main Patel Rd  
New Delhi 110 008  
Ph:011-25884903/4  
Fax: 011- 25884422  
email:Delhi@fosroc.com

##### Kolkata

30/B Jodhpur Park  
Ground Floor  
Kolkata 700 068  
Ph: 033 2472 5482  
Fax: 033-2472 9921  
email:Kolkata@fosroc.com

●Ahmedabad : (079) 26762799 ●Ankleshwar : (02646) 220704/224687 ●Bhubaneshwar : (0674) 2521176 ●Chennai (044) 24899949/24853383  
●Chandigarh : (0172) 2639360 ●Cochin : (0484) 2356668 ●Coimbatore : (0422) 2472966 ●Goa : (0832) 2542465 ●Guwahati (0361) 2548793  
●Hyderabad : (040) 27662324/27662425 ●Hubli (0836) 3402597 ●Indore : (0731) 504339/5061477 ●Jaipur : (0141) 2235349 ●Lucknow : (0522) 22239044 ●Nagercoil (04652) 2224849 ●Mangalore: (0824) 22272234 ●Visakhapatnam : (0891) 2564850

INDIA/2004/0845/A

